



Technical Specifications

Dimension

| Power | 60W | 100W | 120W | 150W | 200W | 300W | 400W |
|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Size (mm) | 105*50*24 | 135*50*24 | 170*50*24 | 205*50*24 | 237*50*24 | 225*60*28 | 225*60*28 |

Output

| Power | 60W | 100W | 120W | 150W | 200W | 300W | 400W |
|-----------------------------|-----------|-----------|----------|------------|-----------|----------|------------|
| Output Current (Loading) | 2.5A±0.2A | 4.1A±0.2A | 5A±0.25A | 6.25A±0.3A | 8.3A±0.4A | 12A±0.6A | 16.5A±0.8A |
| Output Voltage (No Loading) | 24V±0.5V | 24V±0.5V | 24V±0.5V | 24V±0.5V | 24V±0.5V | 24V±0.5V | 24V±0.5V |
| Efficiency | ≥95% | ≥95% | ≥95% | ≥95% | ≥95% | ≥95% | ≥95% |

Performance Testing

| Power | 60W | 100W | 120W | 150W | 200W | 300W | 400W |
|---------------------|-----------|-----------|----------|------------|-----------|----------|------------|
| Output Voltage | 24V±0.5V | 24V±0.5V | 24V±0.5V | 24V±0.5V | 24V±0.5V | 24V±0.5V | 24V±0.5V |
| Max. Output Current | 2.5A±0.2A | 4.1A±0.2A | 5A±0.25A | 6.25A±0.3A | 8.3A±0.4A | 12A±0.6A | 16.5A±0.8A |
| Max. Power | 60W | 100W | 120W | 150W | 200W | 300W | 400W |
| Short-circuit | OK | OK | OK | OK | OK | OK | OK |
| Over loading | Adaptive | Adaptive | Adaptive | Adaptive | Adaptive | Adaptive | Adaptive |

Descriptions

- Parameter : 24 V
- Housing Material : Aluminum
- Rated Voltage : AC220V
- Input Voltage : AC180-265V
- Frequency : 50~60Hz
- Power Factor : ≥0.6
- IP : IP20
- Short-circuits protect : Output short-circuited for 3 seconds, then connect powered on again, and it can work normally
- Working Temperature : -30C~+40C
- Input Voltage : AC220V
- Input-Housing : AC 1.5kV/5mA 1Min
- Input-Output : AC 1kV/5mA 1Min