


Geroluxe Code


ZO-CL003



Photometrics



Color Temp. Beam Angle



Technical Specifications

Dimension(mm)	Power	Luminous flux	Finishing	Colour Type
A25 X B35 X C32mm	25W	2750lm	Black / White	(One/3) colour
A40 X B35 X C32mm	40W	4400lm	Black / White	(One/3) colour
A60 X B35 X C32mm	60W	6600lm	Black / White	(One/3) colour
A80 X B35 X C32mm	80W	8800lm	Black / White	(One/3) colour
A100 X B35 X C32mm	100W	11000lm	Black / White	(One/3) colour

Product Features:

Girolux pendant offers another option for contemporary indoor lighting solutions. Surrounded by a aluminum profile structure, with durable white powder coat finish, Opal Polycarbonate diffuser, offering a comfortable diffused light, High transmission opal diffuser, Suspension installation.

Description:

- Housing: Aluminum Die-cast
- Diffuser: Opal Polycarbonate
- Color Available: White, Black
- Lifespan: >50,000 Hours (L80 B10)
- Reflector: Aluminum Reflector
- Voltage: AC200-240V
- Working Temperature: -30C°~ + 65C°
- UGR < 22
- Luminous Efficacy (lm/W): 110
- MacAdam < 3

Technical Drawing

