



Geroluxe Code

ZO-HF001



D003-8/8W/110°


Color Temp.



Beam Angle



Technical Drawing



Technical Specifications

Dimension(mm)	Cut Out(mm)	Power	Luminous flux	Input Voltage	Finishing Color
Φ85x36	Φ70	8W	560lm	220-240V	Black / White
Φ100x36	Φ89	12W	960lm	220-240V	Black / White
Φ110x36	Φ100	15W	1200lm	220-240V	Black / White
Φ140x38	Φ125	20W	1800lm	220-240V	Black / White
Φ155x38	Φ140	24W	2160lm	220-240V	Black / White
Φ165x38	Φ150	30W	2700lm	220-240V	Black / White
Φ215x41	Φ200	40W	3600lm	220-240V	Black / White

Product Features:

1. Quality famous branded LED SMD chip, high luminous efficiency, CRI>80/90, lower thermal diffusivity to provide uniform & comfortable light layout.
2. Patented appearance design. High quality aluminum heat sink to ensure ingenious shape and increase heat dissipation space.
3. High quality imported acrylic diffuser to achieve uniform light and high lumen.
4. High quality isolated constant current driver fixed on housing to ensure efficient installation.
5. Dimensions range from 2.5"-8", Powers ranging from 8W-40W.
6. Lifespan up to 50,000 hours, 5 years warranty.



SMD
Dip Switch 3CCT

● WW Warm White ● DL Day Light ● CW Cool White



Ultra thin design, serialized SMD/COB products, covering 2.5" - 8" in size.