

Code


ZO-MLF0018



Technical Specifications

Dimension(mm)	Power	Luminous flux	lm/W
Φ 686 x 72 x 63	1 x 10W	1100	110
Φ 670 x 96 x 60	2 x 10W	2200	110
Φ 1295 x 72 x 63	1 x 18W	1980	110
Φ 1270 x 96 x 60	2 x 18W	3960	110
Φ 1595 x 72 x 63	1 x 24W	2640	110
Φ 1570 x 96 x 60	2 x 24W	5280	110


Light Distribution



Beam Angle: 110°


Color Temp.

Beam Angle



110°

Technical Drawing



Product Features:

- Resistant to Corrosion
- Easy to Install and maintain
- High Luminous Efficacy
- Rated lifetime: 30,000 Hours
- LED Type: T8 LED Tube
- Voltage/ Frequency: 220-240V/50Hz
- Power: 2x18W
- Input Voltage: 220-240V/50Hz
- Beam Angle: 110°
- Mounting options: 1- Suspension mounting
- 2- Ceiling mounting
- Lamp Holder: G13
- Product Size (L x W x H): 1270x90x60mm

- Product Material: Diffuser : PC
Housing: ABS
Clips: Stainless Steel

- Package: MEAS : 1300x276x300mm
N.W: 13.2KGS
G.W: 14.2KGS
QTY: 12PCS

Environmental

- IP Rating: IP65
- Operating Temperature: -20°C to 50°C
- Operating humidity: 0 to 95%

