

Geroluxe Code

ZO-STS-090




Technical Specifications

Lumen/m	4.8W	9.6W	14.4W	19.2W	24W
2700K	474	908	1304	1727	2126
3000K	489	930	1325	1767	2209
4000K	504	952	1404	1865	2296
6500K	516	962	1406	1879	2304
Max. Run Length-(M)	5	5	5	5	5

-
-
-
-
-
-
-
-
-
-
-
-

Color Temp.



Product Features

- Field cuttable
- Operates at safe and energy-efficient voltage of DC24V
- Slim and elegant, ideal for indoor applications
- 3M tape on the back makes it easy to install
- Available in a variety of CCT color options
- 5 years warranty

Description

PCB Width	10mm
LED Pitch	8.3mm
Cutting Interval	50mm
LED Brand	Sanan
LED Size	2835
LED Quantity	120 LEDs/m
Housing Material	N/A
Housing Technique	Surface Coating
Adhesive Type	Yellow 3M tape
Feed Entry	Front
Feed Length	Standard length 15cm
Storage Temperature	-25~60°C (-13~140°F)
Ambient Temperature	-20~45°C (-4~113°F)
Max Production Length	30m

Voltage	24VDC (23.5Vmin, 24.5Vmax)
Beam Angle	120°
MacAdam	3 steps
Efficacy (lm/W)	90lm/W @4000K
CRI	Ra90
Lumen Maintenance	> 54,000 hours
IP Rating	IP65
Resistance	UV, solvent, saltwater, flame
Dimming	Triac, ELV, PWM, 0-10V, DMX
Warranty	5 years

Technical Drawing

