



### Geroluxe Code



#### Color Temp.



#### Technical information

Dimension(mm)	Power	Voltage	Finishing Color
350*12mm	150W	150-200lm/W	Black
383*125mm	200W	150-200lm/W	Black

Hollow heat sink design increase more airflow for better heat dissipation

High lumen LED, with 50,000hrs lifespan

Imported optical lens, its luminous efficiency up to 95%

High quality aluminum alloy, anti-corrosion, substantial, durable, artistic, practical. High craft manifesting production value of famous brand

Designed diamond face reflection process, super high efficiency reflection light source, effectively enhance the brightness of the illumination.

#### Product benefits

Energy saving thanks to 160lm/w system efficacy;

Die-cast housing, UV resistant PC lens offer a durable service;

Long 100,000hrs lifetime reduces maintenance costs;

Safety compliance certificates: CB, EMC RoHS 2.0

Available in, 150w and 200w

100-277V AC input;


Standard CCT: Standard 6500K

High color rendering: CRI > 80

High power factor: PF>0.90

160lm/w, 50,000hrs lifespan

IP65, IK08 protected



Dist (M)	Enadir (lx)
10m	52.29
20m	13.07
30m	5.810
40m	3.268
50m	2.092



A variety of lenses are available



#### Driver Brand Philips



#### Lumileds Chips

